


Keystone Inline Coupler CC6S2

Cat.6, unshielded



PRODUKTBESCHREIBUNG

Geschirmter RJ45-Keystone-Inline-Coupler aus verzinktem Blech. Geeignet für alle Anwendungen (Sprache und Daten) der Klasse E/ 250 MHz bis 1 GbE.

PRODUCT DESCRIPTION

Shielded Keystone RJ45 inline coupler made of galvanized sheet metal. Suitable for all applications (voice and data) Class E/ 250 MHz up to 1 GbE.

ÜBERTRAGUNGSEIGENSCHAFTEN

Cat.6, Klasse E, 250 MHz/ 1 GbE

GELTENDE NORMEN

EIA/TIA 568 C.2 Cat.6
ISO/IEC 11801 (2nd ed.)
EN 50173 2. Ausgabe

TRANSMISSION CHARACTERISTICS

Cat.6, Class E, 250 MHz/ 1 GbE

APPLICABLE STANDARDS




EIA/TIA 568 C.2 Cat.6
ISO/IEC 11801 (2nd ed.)
EN 50173 2. Edition

AUFBAU

Maße (HxBxT)	23,5 x 17,05 x 28,55 mm
Gehäuse	PC/ABS (UL-94V0)
Leiterplatte	FR4, UL-94V0
Steckkraft	≤ 30 N
Steckzyklen	min. 750
Isolationswiderstand	500 mΩ
Kontaktwiderstand	20 mΩ
Max. Nennstrom	1,5 Amps
PoE	PoE nach IEEE802.3at

CONSTRUCTION

Dimension (HxWxD)	23,5 x 17,05 x 28,55 mm
Housing	PC/ABS (UL-94V0)
Circuit Board	FR4, UL-94V0
Plug Tension	≤ 30 N
Insertion Cycle	min. 750
Isolation resistance	500 mΩ
Contact resistance	≤ 20 mΩ
Ampacity	1,5 Amps
PoE	PoE acc. IEEE802.3at



BESTELLINFORMATION/ ORDERINFORMATION

Typennummer/ Type Number
Artikelbezeichnung/
Item Description

20315
CC6S2 Keystone Inline Coupler Cat.6 unshielded