

# PRO400-21 Patch Cord

Cat.6 U/FTP AWG27 LSOH/FRNC




## PRODUCT DESCRIPTION

AIXONTEC® PRO 400-21, Cat.6 RJ45 shielded patch cords are made of bare copper stranded cable and Hirose TM21 plugs. The high quality stranded cable with U/FTP construction has a foil pair shielding (PiMF) construction and is tested up to a frequency of 400 Mhz. The AIXONTEC® PRO 400-21 patch cords are most suitable for Voice, Video and Data-Applications of Class E/ 250MHz up to 1 Gigabit Ethernet. Available in different colors and lengths. We recommend our color coding rings for more efficient port assignment

## TECHNICAL INFORMATION

Electrical values	Cat.6 (ISO/IEC) Class E
Norms	ISO/IEC 11801 / EN 50173
Flame retardancy	IEC 60332-1/ IEC 60754-2 / IEC 61034
Cable construction	Cat.6 4x2xAWG27/7 U/FTP Foil pair shielding (PiMf), 400 Mhz tested.
Plug	Hirose TM21 RJ45 Cat.6 shielded, 50µ gold plated contacts
Pin assignment	1:1,Crossover on request
Cable diameter	5,5 mm
Outer sheath	LSOH/FRNC in grey, halogen free, low smoke density and flame retardant.
Boot	Original Hirose TM21 boots in in grey/ red/ yellow/ green/ blue



## ORDERING INFORMATION

Type number	20110
Item description	PRO400-21 Cat.6 U/FTP AWG27 LSOH/FRNC Other lengths and colors on request

## ACCESSORIES (Optionally)

21201	Color coding rings (PU: 100 pcs., in 10 different colors)
-------	---



Länge (m)	Black	Grey	Red	Yellow	Green	Blue
0,5	20110.BK0,5	20110.GR0,5	20110.RD0,5	20110.YL0,5	20110.GN0,5	20110.BL0,5
1,0	20110.BK1,0	20110.GR1,0	20110.RD1,0	20110.YL1,0	20110.GN1,0	20110.BL1,0
1,5	20110.BK1,5	20110.GR1,5	20110.RD1,5	20110.YL1,5	20110.GN1,5	20110.BL1,5
2,0	20110.BK2,0	20110.GR2,0	20110.RD2,0	20110.YL2,0	20110.GN2,0	20110.BL2,0
3,0	20110.BK3,0	20110.GR3,0	20110.RD3,0	20110.YL3,0	20110.GN3,0	20110.BL3,0
4,0	20110.BK4,0	20110.GR4,0	20110.RD4,0	20110.YL4,0	20110.GN4,0	20110.BL4,0
5,0	20110.BK5,0	20110.GR5,0	20110.RD5,0	20110.YL5,0	20110.GN5,0	20110.BL5,0
7,5	20110.BK7,5	20110.GR7,5	20110.RD7,5	20110.YL7,5	20110.GN7,5	20110.BL7,5
10,0	20110.BK10,0	20110.GR10,0	20110.RD10,0	20110.YL10,0	20110.GN10,0	20110.BL10,0
12,0	20110.BK12,0	20110.GR12,0	20110.RD12,0	20110.YL12,0	20110.GN12,0	20110.BL12,0
15,0	20110.BK15,0	20110.GR15,0	20110.RD15,0	20110.YL15,0	20110.GN15,0	20110.BL15,0
20,0	20110.BK20,0	20110.GR20,0	20110.RD20,0	20110.YL20,0	20110.GN20,0	20110.BL20,0
25,0	20110.BK25,0	20110.GR25,0	20110.RD25,0	20110.YL25,0	20110.GN25,0	20110.BL25,0
30,0	20110.BK30,0	20110.GR30,0	20110.RD30,0	20110.YL30,0	20110.GN30,0	20110.BL30,0
35,0	20110.BK35,0	20110.GR35,0	20110.RD35,0	20110.YL35,0	20110.GN35,0	20110.BL35,0
50,0	20110.BK50,0	20110.GR50,0	20110.RD50,0	20110.YL50,0	20110.GN50,0	20110.BL50,0