

PRO900M-21 Patch Cord


Cat.6/Class E_A S/FTP AWG27/7 LSOH/FRNC



LEONI



Delivered as standard with production date and cable length-label.



PRODUCT DESCRIPTION

AIXONTEC® PRO900M-21 double shielded (S/FTP) Cat.6/Class E_A RJ45 Patch cords are made of bare copper with fully molded boots and latch protection. The high quality shielded Hirose-TM-21 plug, coupled with a brilliant 900 MHz stranded cable, results in an absolutely high quality patch cord. The molded construction makes this patch cord ideally suitable for a reliable and robust high performance. The AIXONTEC® PRO900M Patch cords are most suitable for Voice, Video and Data-Applications of Class E_A/ 500MHz up to 10 Gigabit Ethernet. Available in different colors and lengths. We recommend our color coding rings for more efficient port assignment.

TECHNICAL INFORMATION

Electrical values	Cat.6 (ISO/IEC) Class E _A
Norms	ISO/IEC 11801 / EN 50173 / Flame retardant according to IEC 60332-
Flame retardant	IEC 60332-1-2/ IEC 60754-1/2 / IEC 61034-1/2
Cable construction	Cat.7 4x2xAWG27/7 S/FTP Over all braid shielding and pair shielding (PiMf)
Plug	Hirose TM21 RJ45 Cat.6 shielded 50µ gold plated contacts
Pin assignment	1:1,Crossover on request
Cable diameter	5,5 mm
Outer sheath	LSOH/FRNC in blue color, halogen free, low smoke density and flame retardant
Boot	Fully molded boots made of halogen free material in blue color.



ORDERING INFORMATION

Typen-Nummer	20113
Item description	PRO900M-21 Cat.6 S/FTP AWG27 LSOH/FRNC <i>Other lengths and colors on request</i>

ACCESSORIES (optionally)

21201	Color coding rings (PU: 100 pcs., in 10 different colors)
-------	---



Length (m)	Blue
0,5	20113.BL0,5
1,0	20113.BL1,0
1,5	20113.BL1,5
2,0	20113.BL2,0
2,5	20113.BL2,5
3,0	20113.BL3,0
4,0	20113.BL4,0
5,0	20113.BL5,0
6,0	20113.BL6,0
7,0	20113.BL7,0
8,0	20113.BL8,0
9,0	20113.BL9,0
10,0	20113.BL10,0
12,0	20113.BL12,0
15,0	20113.BL15,0
20,0	20113.BL20,0