

Hirose TM21/TM31 RJ45-Plug

shielded plugs with cable tensil strength.



PRODUCT DESCRIPTION

Shielded Hirose TM21 RJ45 plug with 50µ goldplated contacts incl. wire manager.

DATA PERFORMANCE

Hirose TM21 : Cat.6 250MHz 1GbE / (ISO/IEC)

Hirose TM31 : Cat.6_A 500MHz 10GbE / (ISO/IEC)

CONSTRUCTION

Housing	nickel plated brass
Contacts	50µ gold plated
Cable acceptance	AWG 23-26
Tension	30≤N
Insertion cycle	min. 750
Isolation resistance	500mΩ
Contact resistance	≤20mΩ
Max. ampacity	1,5 Amps
Operation temperature	-40° bis 70°C



ORDERING INFORMATION TM21

Type number	20404
Item description	Hirose TM 21 RJ45 Plug Cat.6 shielded
Packaging unit	min. 100 pcs.

ORDERING INFORMATION TM31

Type number	20405
Item description	Hirose TM 31 RJ45 plug Cat.6A geschirmt
Packaging unit	min. 100 pcs.

Hirose Boot

für Hirose TM21/TM31 RJ45-Plug

PRODUCT DESCRIPTION

Original Hirose boot for Hirose TM21 or TM31 plug.

CONSTRUCTION

Material	Polycarbonate, PC/ABS
Cable diameter	5,0-6,0 mm



Black	20503.BK	Green	20503.GN
Red	20503.RD	White	20503.WI
Orange	20503.OR	Grey	20503.GR
Yellow	20503.YL	Blue	20503.BL

ORDERING INFORMATION

Type number	20503
Item description	Boot Hirose TM21/TM31
Packaging unit	min. 10 pcs.